



PRODUCT DATA SHEET

Fully Synthetic Petrol Engine Oil
SAE 5W-30 API SN/CF

Description:

Fully Synthetic Petrol Engine Oil SAE 5W-30 API SN/CF is fully synthetic motor oil formulated to provide exceptional wear protection in hot or cold operating temperatures. Provides protection for extended oil drains, heavy loads and for vehicles requiring synthetic motor oil. **SAE 5W-30** meets the requirements of API SN. It provides exceptional performance in extreme cold temperatures.

Benefits:

- **Easy cold weather starting** due to excellent low temperature properties of the synthetic base oils.
- **Minimizes engine deposit and emissions** under heavy duty and stop-and-go driving conditions.
- **Promotes long engine life** due to extremely fast lubrication during starting, and outstanding wear protection during all other engine operating conditions.

Application:

Fully Synthetic Petrol Engine Oil SAE 5W-30 API SN/CF is recommended for all types of modern vehicles and multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks where the manufacturer recommends an API SN or earlier specification.

Typical Characteristic:

PARAMETERS	UNIT	Typical Specs.	TEST METHODS
Kinematic Viscosity @ 100°C	mm ² /s	9.3 – 12.5	ASTM D7042
Viscosity Index	-	Min. 160	ASTM D2270
Total Base Number,	mg KOH/g	Min. 6	ASTM 2896
Flash Point	°C	Min. 190	ASTM D93
Pour Point	°C	Max. -35	ASTM D97
CCS @-30°C	cP	Max. 6600	ASTM D5293



Product Performance Claim:

API SM/SN/CF

Safety Information:

Fully Synthetic Petrol Engine Oil SAE 5W-30 API SN/CF is unlikely to present any significant health or safety hazard when properly used in recommended application and if good standards of industrial and personal hygiene are maintained.

- **Eye:** If irritation or redness develops, flush eyes with clean water. If symptoms persist, seek medical attention.
- **Skin:** Wipe material from skin and wash with mild soap and clean water. If irritation or redness develops, seek medical attention.

Storage:

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should be kept in a cool, dry, well ventilated place not above 60 degree Celsius.

Protect the Environment:

Dispose used oil to an authorized collection point in compliance to the local authority regulation. Do not discharge used oil into drains, soil or water.